


## **DESIGN NOTES: AN6-15A AIRFRAME BOLT**

- 1. LENGTH 1-45/64" (1.703"), GRIP 1-1/16" (1.062"), THREAD 3/8-24 UNF-3A.
- 2. PROCUREMENT SPECIFICATION NASM6812.
- 3. MATERIAL ALLOY STEEL PER PROCUREMENT SPECIFICATION. UNS G40370 AMS6300 DFAR EXEMPT UNS G87400 AMS6322 DFAR APPLIES UNS G41400 AMS6382 DFAR APPLIES UNS G41300 AMS-S-6758 DFAR APPLIES
- 4. HEAT TREAT AMS-2759 HRC 26-32.
- 5. FINISH CADMIUM PLATED PER AMS-QQ-P-416, TYPE 2 (YELLOW), CLASS 2.
- 6. THREADS 3/8-24 UNF-3A ROLLED PROCESS PER MIL-S-7742.
- 7. TENSILE 10,100 LBS. [44,927 N] MIN.
- 8. YIELD 7,740 LBS. [34,429 N] MIN.
- 9. SINGLE SHEAR 8,280 LBS. [36,831 N] MIN. SHORT LENGTH N/A.





**ACTUAL SIZE** 

## **UNCONTROLLED**

CONFORMS TO: NASM3 THRU NASM20 PART NUMBER: AN6-15A

		PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS STRICTLY PROHIBITED.			AIRFASCO.COM 2655 HARRISON AVE SW, CANTON, OHIO 44706 USA					
		APPRO'	PROVALS DATE		PART	AN6-I5A_AFC6-I5C2				
ANGLES	±5°	DRAWN	C.D.	6/10/13	NUMB	NUMBER: ANO-13A_AFCO-13CZ				
.XX.	±.03"	CHECKED	T.W.	6/10/13	SIZE	MATE	RIAL:	EST. WEIGHT:		
.XXX	±010"	ENG APPR	B.E.	6/10/13	] A		4037 / 8740 OR AS NOTED	.066 / EA	CH LBS. [30	0.0 g]
.XXXX	±.001"	MGR APPR	D.D.	6/10/13	SCALE:	2X	DRAWING NUMBER: AN6-15A_A	AFC6-15C2	SHEET I O	FI