



SCALE: 0.75X

DESIGN NOTES: AN6-63A AIRFRAME BOLT

1. LENGTH 6-29/64" (6.453"), GRIP 5-13/16" (5.812"), THREAD 3/8-24 UNF-3A.
2. PROCUREMENT SPECIFICATION NASM6812.
3. MATERIAL ALLOY STEEL PER PROCUREMENT SPECIFICATION.
 UNS G40370 AMS6300 DFAR EXEMPT
 UNS G87400 AMS6322 DFAR APPLIES
 UNS G41400 AMS6382 DFAR APPLIES
 UNS G41300 AMS-S-6758 DFAR APPLIES
4. HEAT TREAT AMS-2759 HRC 26-32.
5. FINISH CADMIUM PLATED PER AMS-QQ-P-416, TYPE 2 (YELLOW), CLASS 2.
6. THREADS 3/8-24 UNF-3A ROLLED PROCESS PER MIL-S-7742.
7. TENSILE 10,100 LBS. [44,927 N] MIN.
8. YIELD 7,740 LBS. [34,429 N] MIN.
9. SINGLE SHEAR 8,280 LBS. [36,831 N] MIN. SHORT LENGTH N/A.



ACTUAL SIZE

EXAMPLE PART NUMBER

AFC 6-63 C2 CADMIUM TYPE 2 YELLOW PLATING
AFC 6-63 C1 CADMIUM TYPE 1 PLAIN WHITE PLATING
AFC 6-63 TDC THERMAL DIFFUSION COATED ASTM A1059

↑ FINISH
 ↑ LENGTH 6.453"
 ↑ BODY SIZE & THREAD .375-24 UNF-3A
 ↑ MANUFACTURER AIRFASCO

UNCONTROLLED

CONFORMS TO: NASM3 THRU NASM20
 PART NUMBER: AN6-63A

DIMENSIONS ARE IN INCHES AND TOLERANCES ARE AS SHOWN BELOW. DIMENSIONAL TOLERANCES AND SYMBOLS PER ANSI Y14.5M-1982	PROPRIETARY PARTS SHOWN IN THIS DRAWING ARE THE SUBJECT OF ISSUED UNITED STATES AND FOREIGN PATENTS AND PATENTS PENDING. UNAUTHORIZED REPRODUCTION AND/OR DISTRIBUTION OF THIS DRAWING IS STRICTLY PROHIBITED.		AIRFASCO.com 2655 HARRISON AVE SW, CANTON, OHIO 44706 USA	
	APPROVALS DRAWN M.B. DATE 3/25/14 CHECKED T.W. DATE 3/25/14 ENG APPR B.E. DATE 3/25/14 MGR APPR D.D. DATE 3/25/14		PART NUMBER: AN6-63A_AFC6-63C2	REV
ANGLES ±5° .XX ±.03" .XXX ±.010" .XXXX ±.001"	MATERIAL: 4037 / 8740 OR AS NOTED		EST. WEIGHT: .219 / EACH LBS. [99.6 g]	
SCALE: 0.75X		DRAWING NUMBER: AN6-63A_AFC6-63C2		SHEET 1 OF 1